Ve-Zer-5103-en / 01 06 203

Certificate of Constancy of Performance



Certificate No.: 0757-CPR-229EG-7051574-5-8

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

Door hinges

Product description/ specification Easy 3D-00-XX

According to configuration in annex 1

Levels and classes of performance

According to configuration in annex 1

Intended use(s)

Intended for use on doors in escape routes with requirements for

fire resistance and smoke control

placed on the market under the name or trade mark of

SFS Group Italy S.r.I. unipersonale

Via Castelfranco Veneto, 71, IT-33170 Pordenone

and produced in the manufacturing plant(s)

SFS Group Italy S.r.I. unipersonale Via Castelfranco Veneto, 71, IT-33170 Pordenone

Notified body No. EC-Reference-No.

0757

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 1935: 2002

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the **constancy of performance of the construction product.**

This certificate was first issued on 22.01.2014 and will remain valid until 20.04.2026, as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

The use of this certificate and the marking of the products are bound by an existing certification and surveillance contract with the **ift** Rosenheim no. 229EG 7051574.

Christian Kehrer

Head of notified product certification body

ift Rosenheim 21.04.2023





EN 1935-2002-02/AC:2003-12











www.ec.europa.eu

Identity check



www.ift-rosenheim.de/ ift-zertifiziert ID: FB1-EB03E



Annex 1 Page 1 of 9

Certificate holder: SFS Group Italy S.r.l. unipersonale

Date of issue: 21.04.2023





Compilation of hinges

No. 1:

Product designation: **Easy 3D-00-00**Hinge type: 3-part door hinge

Material: Frame zinc die-cast and steel

sash aluminium

Bearing Technology: maintenance-free slide bearing technology

Fastening: milled and screw-fitted into frame

milled and screw-fitted into sash

Test report: 205 31004 of 24.03.2006

IBS 06020101 of 19.02.2008

| Classification: | 3 | 7 | 4 | 1 | 1 | *) | 0 | 11

Intended use: Intended for use on doors in escape routes with requirements for fire

resistance and smoke control

*) Allocation of the corrosion resistance for hinges as a function of the surfaces

No.	Hinge surface	Corrosion resistance according to	
		DIN EN 1670-1998-12	
1	Plastic-coated	4	
2	Anodised aluminium	4	
3	Bronze	4	
4	brass	4	
5	nickel-plated	4	

Annex 1 Page 2 of 9

Certificate holder: SFS Group Italy S.r.l. unipersonale

Date of issue: 21.04.2023





No. 2:

Product designation: Easy 3D-00-20

Hinge type: 3-part door hinge with lateral height adjustment

Material: Frame zinc die-cast and steel

sash aluminium

Bearing Technology: maintenance-free slide bearing technology

Fastening: milled and screw-fitted into frame

milled and screw-fitted into sash

Test report: 13-001910-PR01 of 27.11.2013

 Classification:
 3
 7
 4
 1
 1
 4
 0
 11

Intended use: Intended for use on doors in escape routes with requirements for fire

resistance and smoke control

No. 3:

Product designation: Easy 3D-00-21

Hinge type: 3-part door hinge with lateral height adjustment

Material: Frame zinc die-cast and steel

sash aluminium

Bearing Technology: maintenance-free slide bearing technology

Fastening: milled and screw-fitted into frame

milled and screw-fitted into sash

Test report: 13-001910-PR01 of 27.11.2013

 Classification:
 3
 7
 4
 1
 1
 4
 0
 11

Intended use: Intended for use on doors in escape routes with requirements for fire

Annex 1 Page 3 of 9

Certificate holder: SFS Group Italy S.r.l. unipersonale

Date of issue: 21.04.2023





N	lo.	4
	•	_

Product designation: Easy 3D-00-22

Hinge type: 3-part door hinge with lateral height adjustment

Material: Frame zinc die-cast and steel

sash aluminium

Bearing Technology: maintenance-free slide bearing technology

Fastening: milled and screw-fitted into frame

milled and screw-fitted into sash

Test report: 13-001910-PR01 of 27.11.2013

 Classification:
 3
 7
 4
 1
 1
 4
 0
 11

Intended use: Intended for use on doors in escape routes with requirements for fire

resistance and smoke control

No. 5:

Product designation: Easy 3D-00-23

Hinge type: 3-part door hinge with lateral height adjustment

Material: Frame zinc die-cast and steel

sash aluminium

Bearing Technology: maintenance-free slide bearing technology

Fastening: milled and screw-fitted into frame

milled and screw-fitted into sash

Test report: 13-001910-PR01 of 27.11.2013

 Classification:
 3
 7
 4
 1
 1
 4
 0
 11

Intended use: Intended for use on doors in escape routes with requirements for fire

Annex 1 Page 4 of 9

Certificate holder: SFS Group Italy S.r.l. unipersonale

Date of issue: 21.04.2023





No. 6:

Product designation: Easy 3D-00-24

Hinge type: 3-part door hinge with lateral height adjustment

Material: Frame zinc die-cast and steel

sash aluminium

Bearing Technology: maintenance-free slide bearing technology

Fastening: milled and screw-fitted into frame

milled and screw-fitted into sash

Test report: 13-001910-PR01 of 27.11.2013

 Classification:
 3
 7
 4
 1
 1
 4
 0
 11

Intended use: Intended for use on doors in escape routes with requirements for fire

resistance and smoke control

No. 7:

Product designation: Easy 3D-00-25

Hinge type: 3-part door hinge with lateral height adjustment

Material: Frame zinc die-cast and steel

sash aluminium

Bearing Technology: maintenance-free slide bearing technology

Fastening: milled and screw-fitted into frame

milled and screw-fitted into sash

Test report: 13-001910-PR01 of 27.11.2013

 Classification:
 3
 7
 4
 1
 1
 4
 0
 11

Intended use: Intended for use on doors in escape routes with requirements for fire

Annex 1 Page 5 of 9

Certificate holder: SFS Group Italy S.r.l. unipersonale

Date of issue: 21.04.2023





No. 8:

Product designation: Easy 3D-00-26

Hinge type: 3-part door hinge with lateral height adjustment

Material: Frame zinc die-cast and steel

sash aluminium

Bearing Technology: maintenance-free slide bearing technology

Fastening: milled and screw-fitted into frame

milled and screw-fitted into sash

Test report: 13-001910-PR01 of 27.11.2013

 Classification:
 3
 7
 4
 1
 1
 4
 0
 11

Intended use: Intended for use on doors in escape routes with requirements for fire

resistance and smoke control

No. 9:

Product designation: Easy 3D-00-27

Hinge type: 3-part door hinge with lateral height adjustment

Material: Frame zinc die-cast and steel

sash aluminium

Bearing Technology: maintenance-free slide bearing technology

Fastening: milled and screw-fitted into frame

milled and screw-fitted into sash

Test report: 13-001910-PR01 of 27.11.2013

Classification: 3 7 4 1 1 4 0 11

Intended use: Intended for use on doors in escape routes with requirements for fire

Annex 1 Page 6 of 9

Certificate holder: SFS Group Italy S.r.l. unipersonale

Date of issue: 21.04.2023





No. 10:

Product designation: Easy 3D-00-28

Hinge type: 3-part door hinge with lateral height adjustment

Material: Frame zinc die-cast and steel

sash aluminium

Bearing Technology: maintenance-free slide bearing technology

Fastening: milled and screw-fitted into frame

milled and screw-fitted into sash

Test report: 13-001910-PR01 of 27.11.2013

 Classification:
 3
 7
 4
 1
 1
 4
 0
 11

Intended use: Intended for use on doors in escape routes with requirements for fire

resistance and smoke control

No. 11:

Product designation: Easy 3D-00-30

Hinge type: 3-part door hinge with lateral height adjustment

Material: Frame zinc die-cast and steel

sash aluminium

Bearing Technology: maintenance-free slide bearing technology

Fastening: milled and screw-fitted into frame

screwed onto sash

Test report: 13-001910-PR01 of 27.11.2013

 Classification:
 3
 7
 4
 1
 1
 4
 0
 11

Intended use: Intended for use on doors in escape routes with requirements for fire

Annex 1 Page 7 of 9

Certificate holder: SFS Group Italy S.r.l. unipersonale

Date of issue: 21.04.2023





No. 12:

Product designation: Easy 3D-00-33

Hinge type: 3-part door hinge with lateral height adjustment

Material: Frame zinc die-cast and steel

sash steel

Bearing Technology: maintenance-free slide bearing technology

Fastening: milled and screw-fitted into frame

screwed onto sash

Test report: 19-004367-PR01 of 12.12.2019

 Classification:
 3
 7
 4
 1
 1
 4
 0
 11

Intended use: Intended for use on doors in escape routes with requirements for fire

resistance and smoke control

No. 13:

Product designation: Easy 3D-00-34

Hinge type: 3-part door hinge with lateral height adjustment

Material: Frame zinc die-cast and steel

sash aluminium

Bearing Technology: maintenance-free slide bearing technology

Fastening: milled and screw-fitted into frame

screwed onto sash

Test report: 18-002049-PR01 of 14.03.2019

 Classification:
 3
 7
 4
 1
 1
 4
 0
 11

Intended use: Intended for use on doors in escape routes with requirements for fire

Annex 1 Page 8 of 9

Certificate holder: SFS Group Italy S.r.l. unipersonale

Date of issue: 21.04.2023





No. 14:

Product designation: Easy 3D-C-00-20

Hinge type: 3-part door hinge with lateral height adjustment

Material: Frame zinc die-cast and steel

sash aluminium

Bearing Technology: maintenance-free slide bearing technology

Fastening: milled and screw-fitted into frame

milled and screw-fitted into sash

Test report: 19-004367-PR01 of 12.12.2019

 Classification:
 3
 7
 4
 1
 1
 4
 0
 11

Intended use: Intended for use on doors in escape routes with requirements for fire

resistance and smoke control

No. 15:

Product designation: Easy 3D-C-00-25

Hinge type: 3-part door hinge with lateral height adjustment

Material: Frame zinc die-cast and steel

sash aluminium

Bearing Technology: maintenance-free slide bearing technology

Fastening: milled and screw-fitted into frame

milled and screw-fitted into sash

Test report: 19-004367-PR01 of 12.12.2019

 Classification:
 3
 7
 4
 1
 1
 4
 0
 11

Intended use: Intended for use on doors in escape routes with requirements for fire

Annex 1 Page 9 of 9

Certificate holder: SFS Group Italy S.r.l. unipersonale

Date of issue: 21.04.2023





No. 16:

Product designation: Easy 3D-C-00-30

Hinge type: 3-part door hinge with lateral height adjustment

Material: Frame zinc die-cast and steel

sash aluminium

Bearing Technology: maintenance-free slide bearing technology

Fastening: milled and screw-fitted into frame

screwed onto sash

Test report: 19-004367-PR01 of 12.12.2019

 Classification:
 3
 7
 4
 1
 1
 4
 0
 11

Intended use: Intended for use on doors in escape routes with requirements for fire

resistance and smoke control

No. 17:

Product designation: Easy 3D-C-00-34

Hinge type: 3-part door hinge with lateral height adjustment

Material: Frame zinc die-cast and steel

sash aluminium

Bearing Technology: maintenance-free slide bearing technology

Fastening: milled and screw-fitted into frame

screwed onto sash

Test report: 19-004367-PR01 of 12.12.2019

 Classification:
 3
 7
 4
 1
 1
 4
 0
 11

Intended use: Intended for use on doors in escape routes with requirements for fire