Certificate of Constancy of Performance

Certificate No.: 0757-CPR-229PANIK-7031575-2-9

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

Basis:

EN 179:2008-01



Emergency exit devices

Product description/ specification	**Safe E611 Eneo CF, Safe P600, Safe E601-Eneo AF, Safe P603-Tandeo F, Safe A700 Tandeo F, Safe E700 Eneo AF** According to configuration in **annex 1**
Levels and classes of performance	According to configuration in **annex 1**
Intended use(s)	Intended for use on doors in escape routes without requirements for fire resistance and smoke control
placed on the market under the name or trade mark of	**ROTO FRANK AUSTRIA GmbH** Lapp-Finze-Str. 21, AT-8401 Kalsdorf bei Graz
and produced in the manufacturing plant(s)	**ROTO FRANK AUSTRIA GmbH** Lapp-Finze-Str. 21, AT-8401 Kalsdorf bei Graz
Notified body No.	**0757**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 179 : 2008


under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the **constancy of performance of the construction product.**

This certificate was first issued on 26.01.2016 and will remain valid until 25.01.2028, as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

The use of this certificate and the marking of the products are bound by an existing certification and surveillance contract with the **ift** Rosenheim no. 229PANIK 7031575.

Pascal Geiger
Deputy head of the notified product certification body
Certification & Surveillance Body
ift Rosenheim
18.05.2026

ift Rosenheim GmbH
Theodor-Gietl-Str. 7-9
83026 Rosenheim
Germany
Notified Body 0757



www.ec.europa.eu

Identity check

www.ift-rosenheim.de/ift-zertifiziert
ID: 7E4-B475B

Ve-Zer-5107-en / 2025-09

Installation of the emergency exit closures:

For actuation type A (handlebar actuation)

Classification:	**3**	**7**	**5**	**0**	**1**	**3***	**5**	**2**	**A**	**B**

Classification:	**3**	**7**	**5**	**0**	**1**	**3***	**5**	**2**	**A**	**D**

Reference- test reports: No. 15-004017-PR01 dated 26.01.2016 and 04.02.2016
No. 120003793.02 dated 06.12.2011

Lockings:

Designation	Scope	Pin size	Function	Distance	Overlap (in mm)	Strike plates	Hole
Safe E611 Eneo CF	B and D	35 mm up to 80 mm	I	92 mm	F16 F20 F22 F24 U24 U25 U29 U32 U35 U38	F/R strike plate Combination strike plates Special strike plates	PZ

External fitting / internal fitting:

No.	Manufacturer	Coding
1.	Hoppe Holding AG	DO 20.5 DO 20.7 DO 20.20

For actuation type A (handlebar actuation)

Classification:	**3**	**6**	**5**	**0**	**1**	**3**	**2**	**2**	**A**	**B**

Classification:	**3**	**6**	**5**	**0**	**1**	**3**	**2**	**2**	**A**	**D**

Reference – test reports: No. 16-002901-PR01 dated 16.11.2016

Lockings:

Designation	Scope	Pin size	Function	Distance	Overlap (in mm)	Strike plates	Hole
Safe E601-Eneo AF	B and D	35 mm up to 80 mm	I	92 mm	F16 F20 F22 F24 U24 U25 U29 U32 U35 U38	F/R strike plate Automatic strike plates Special strike plates	PZ
Safe P603-Tandeo F							

External fitting / internal fitting:

No.	Manufacturer	Type	Coding
1.	Hoppe Holding AG	FS-86G	
		-/-	DO 20.20.01 DO 20.20.02 DO 20.20.02-RD DO 20.5.01 DO 20.5.02 DO 20.5.02-RD DO 20.7.01 DO 20.7.02

For actuation type A (handlebar actuation)

Classification:	**3**	**7**	**5**	**0**	**1**	**3**	**2**	**2**	**A**	**B**

Classification:	**3**	**7**	**5**	**0**	**1**	**3**	**2**	**2**	**A**	**D**

Reference – test reports: No. 120003793.02 dated 06.12.2011

Lockings:

Designation	Scope	Pin size	Function	Distance	Overlap (in mm)	Strike plates	Hole
Safe P600	B and D	35 mm up to 80 mm	I	92 mm	F16 F20 F22 F24 U24 U25 U29 U32 U35 U38	F/R strike plate Combination strike plates Special strike plates	PZ

External fitting / internal fitting:

No.	Manufacturer	Coding
1.	Hoppe Holding AG	DO 20.5.02 DO 20.7.02 DO 20.20.02
2.	HEWI	DO 20.13.02
3.	FSB	DO 20.3.02

For actuation type A (handlebar actuation)

Classification:	**3**	**7**	**5**	**0**	**1**	**3**	**5**	**2**	**A**	**B**

Classification:	**3**	**7**	**5**	**0**	**1**	**3**	**5**	**2**	**A**	**D**

Reference – test reports: Nr. 23-001998-PR03 dated 12.05.2026

Lockings:

Designation	Scope	Pin size	Function	Distance	Overlap (in mm)	Strike plates	Hole
Safe A700 Tandeo F Safe E700 Eneo AF	B and D	35 mm up to 65 mm	I	92 mm 94 mm	F16 F20 F22 F24 U24 U25 U29 U32 U35 U38	F/R strike plate Combination strike plates Special strike plates	PZ RZ

External fitting / internal fitting:

No.	Manufacturer	Coding
1.	Hoppe Holding AG	DO 20.5.02 DO 20.7.02 DO 20.20.02

Alternative- Special equipment, special designs

1. Safety devices

There is no objection to securing the emergency exit locks with the GFS door guard, EN 179 single-handed version.

Manufacturer: GfS Gesellschaft für Sicherheitstechnik mbH
Tempowerkring 15
21079 Hamburg, Germany

2. Special strike plate/door opener

As an alternative to the standard striking plates, the locks may be operated with electric strike strikes of the series

IST: FT 200, FT 201, FT 500, FT 501, R 7000, R 7001, A 7000
Effeff: 142, 143, 131, 111, 19, 116, 118, 119, 611
DORMA: Fire 447 und Smoke 117

or optionally with the exchange piece

"effeff 14210-00".

Explanations:

Actuation type A:	Latches with “handle actuation”
Actuation type B:	Latches with “push plate actuation”
Area of application class A:	Outward-opening single-leaf escape door, double-leaf escape door: active or passive leaf
Area of application class B:	Single-leaf escape door opening outwards only
Area of application class C: Fixed leaf only	Double-leaf escape door opening outwards:
Area of application class D:	Single-leaf escape door opening inwards only

Description: Self-locking mortise locks with escape door function (panic function) and split cross latch. The bolt is located in the center between the two latch parts.

Function I: One-piece lock nut, permanently active escape door function from the inside. Opening from the inside is always possible via the interior fitting. From the outside, the door can be opened with the key via the changeover.

* With additional feedback contacts integrated in the lock

Function II: Split lock cylinder, permanently active escape door function from the inside. Opening from the inside is always possible via the interior fitting. The exterior fitting or the exterior half of the lock cylinder is electronically controlled to engage or disengage. A special fitting with a split pin is required.

Function IM: One-piece lock nut, permanently active escape door function from the inside. The door can always be opened from the inside using the interior fitting. From the outside, the door can be opened using the key via the changeover. Motorized bolt drive.

* Motorized unlocking of active and passive sashes

Lock cylinder: All types of lock cylinders with a free-running function do not affect proper operation.