

Certificate of Constancy of Performance



Certificate n°: 0757-CPR-277-9045017-1-1

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

Basis:

EN 16034
EN 14351-1

Pedestrian doorsets with fire resistance characteristics

Trade name

M84 FR Alumil

Pedestrian doorsets according to EN 14351-1:2006+A2:2016 with fire resistance characteristics according to EN 16034:2014

Product description/
specification

Classification: see classification reports n°

FIRES-CR-194-21-AUPE dated 05.08.2021
FIRES-CR-195-21-AUPE dated 05.08.2021
FIRES-CR-196-21-AUPE dated 13.09.2021
FIRES-CR-197-21-AUPE dated 13.09.2021
FIRES-CR-291-21-AUPE dated 01.12.2021
FIRES-CR-130-22-AUPE dated 18.07.2022

Levels and classes of performance

According to configuration in **annex 1**

Intended use(s)

- Installation in residential and non-residential construction
- In the case of room partitioning into fire and/or smoke protection sections and/or escape routes

placed on the market under the name or trade mark of

ALUPERFECTION HELLAS A.E.

Industrial Area of Oinofyta, Viotia, GR-32011 Ntamari, Viotia

and produced in the manufacturing plant(s)

ALUPERFECTION HELLAS A.E.

Industrial Area of Oinofyta, Viotia, GR-32011 Ntamari, Viotia

Notified body No.
EC-Reference-No.

0757

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 14351-1:2006+A2:2016 and EN 16034:2014



under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the **constancy of performance of the construction product**.

This certificate was first issued on 11.07.2024 and will remain valid until 10.07.2027, as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

The use of this certificate and the marking of the products are bound by an existing certification and surveillance contract with the **ift Rosenheim** no. 277 9045017.



Gerhard Wackerbauer
Deputy head of product certification
ift Rosenheim
11.07.2024



www.ec.europa.eu

Identity check



www.ift-rosenheim.de/
ift-zertifiziert
ID: B73-C2650

Certificate of constancy of performance

Annex 1 Page 1 of 1
Certificate holder: ALUPERFECTION HELLAS A.E.
Date of issue: 11.07.2024



Certificate n°: 0757-CPR-277-9045017-1-1

Product description:

Essential characteristics according to EN 16034	Performance
Fire resistance (in the case of room partitioning into fire and/or smoke protection sections)	NPD / E 15 / E 20 / E 30 / E 45 / E 60 NPD / EW 15 / EW 20 / EW 30 / EW 45 / EW 60 NPD / EI ₂ 15 / EI ₂ 20 / EI ₂ 30 / EI ₂ 45 / EI ₂ 60* NPD / EI ₁ 15 / EI ₁ 20 / EI ₁ 30 / EI ₁ 45 / EI ₁ 60* ----- * differing classification for glass Polflam: NPD / EI ₂ 15 / EI ₂ 20 / EI ₂ 30 / EI ₂ 45 NPD / EI ₁ 15 / EI ₁ 20 / EI ₁ 30 / EI ₁ 45
Smoke control (only for applications where smoke spread limitation is required)	NPD
Ability to release	NPD / Released
Self-closing action (only for self-closing fire and/or smoke protection doors and/or windows)	NPD / C
Durability of ability to release	NPD / Maintain release
Durability of self-closing (only for self-closing fire and/or smoke protection doors and/or windows) – Compared with loss of quality (resistance to repeated opening and closing) – Compared with ageing (corrosion)	NPD NPD / Achieved