

Certificate of Constancy of Performance



Certificate n°: 0757-CPR-277-6080181-6-2

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

Basis:

EN 16034
EN 14351-1

**External door as per EN 14351-1:2006+
A2:2016 with fire resistance and/or
smoke control as per EN 16034:2014**

Trade name

**Product range "H120 OD"
with trade name
"H120-1 OD" and "H120-2 OD"**

Product description/
specification

Steel, hinged, single and double leaf doors corresponding to EN 14351-1. Construction and classification: see EXAP-reports no. 01653.2/20/R131NZZ and 01653.20/R131NZZ as well as classification reports no. 01653.1/20/R131NZZ and 01653.3/20/R131NZZ

Levels and classes of
performance

According to configuration in **annex 1**

Intended use(s)

- Installation in residential and non-residential construction
- In the case of room partitioning into fire and/or smoke protection sections and/or escape routes

placed on the market
under the name or trade
mark of

Hörmann KG Verkaufsgesellschaft
Upheider Weg 94-98, DE-33803 Steinhagen

and produced in the
manufacturing plant(s)

Hörmann KG Verkaufsgesellschaft
Upheider Weg 94-98, DE-33803 Steinhagen

Notified body No.
EC-Reference-No.

0757

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 14351-1:2006+A2:2016 and EN 16034:2014

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the **constancy of performance of the construction product.**

This certificate was first issued on 09.06.2021 and will remain valid until 08.06.2024, as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

The use of this certificate and the marking of the products are bound by an existing certification and surveillance contract with the **ift** Rosenheim no. 277 6080181.




Prof. Jörn P. Lass
Director

ift Rosenheim
17.06.2021



Christian Kehrer
Head of notified product certification body



www.ec.europa.eu



www.ift-rosenheim.de

Certificate of constancy of performance

Annex 1 Page 1 of 1
 Certificate holder: Hörmann KG Verkaufsgesellschaft
 Date of issue: 17.06.2021



Certificate n°: 0757-CPR-277-6080181-6-2

Product description:

Essential characteristics	Performance	Harmonised technical specification
Fire resistance (Room arrangement in fire and/or smoke control sections)	NPD / E 15 / E 20 / E 30 / E 45 / E 60 / E 90 / E 120 NPD / EW 15 / EW 20 / EW 30 / EW 45 / EW 60 / EW 90 / EW 120 NPD / EI ₂ 15 / EI ₂ 20 / EI ₂ 30 / EI ₂ 45 / EI ₂ 60 / EI ₂ 90 / EI ₂ 120 NPD / EI ₁ 15 / EI ₁ 20 / EI ₁ 30	EN 16034:2014
Smoke protection (only for applications, where limiting the spread of smoke is required)	NPD / S _a / S ₂₀₀	
Ability to release	NPD / released	
Self-closing (only for self-closing fire and/or smoke control door and/or windows)	NPD / C	
Durability of ability to release	NPD	
Durability of self-closing (only for self-closing fire and/or smoke control door and/or windows) – regarding loss of quality (Durability) – regarding aging (Corrosion)	NPD / 0 / 1 / 2 / 3 / 4 / 5 NPD	
Ability to release	Requirement fulfilled	EN 14351-1: 2006+A2:2016