# Certificate of Constancy of Performance



Certificate n°: 0757-CPR-277-6080181-1-2

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

External door as per EN 14351-1:2006+A2:2016 with fire resistance and/or smoke control as per EN 16034:2014

Product range "H3 OD" with trade name "H3-1 OD" and "H3-2 OD"

Single and double leaf steel sheet-side hinged door corresponding to EN 14351-1. Construction and classification see EXAP-report no.: 15-001366-PR01 and classification report no.: 15-001366-PR02.

Hörmann KG Verkaufsgesellschaft

performance According to configuration in annex 1

Installation in residential and non-residential construction
In the case of room partitioning into fire and/or smoke protection

 In the case of room partitioning into fire and/or smoke protection sections and/or escape routes

Placed on the market under the name or trade mark of

Levels and classes of

Intended use(s)

and produced in the manufacturing plant(s)

Notified body No. EC-Reference-No.

Trade name

Upheider Weg 94-98, DE-33803 Steinhagen

Hörmann KG Freisen Bahnhofstraße 43, DE-66629 Freisen

0757

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

#### EN 14351-1:2006+A2:2016 and EN 16034:2014

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the **constancy of performance of the construction product.** 

This certificate was first issued on 29.08.2017 and will remain valid until 28.08.2023, as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

The use of this certificate and the marking of the products are bound by an existing certification and surveillance contract with the **ift** Rosenheim no. 277 6080181.


EN 16034 EN 14351-1

Basis:









www.ec.europa.eu



www.ift-rosenheim.de

Prof. Jörn P. Lass Director ift Rosenheim 29.08.2020

/e-Zer-6274-de / 01.02.2020



Christian / Chris

Christian Kehrer Head of notified product certification body



## **Certificate of constancy of performance**

Annex 1 Page 1 of 1
Certificate holder: Hörmann KG Verkaufsgesellschaft

Date of issue: 29.08.2020



### Certificate n°: 0757-CPR-277-6080181-1-2

#### **Product description:**

Essential characteristics	Performance	Harmonised technical specification
Fire restistance (Room arrangement in fire and/or smoke control sections)	NPD E 15 / E 20 / E 30 El <sub>2</sub> 15 / El <sub>2</sub> 20 / El <sub>2</sub> 30 EW 20 / EW 30	
Smoke protection (only for applications, where limiting the spread of smoke is required)	NPD S <sub>a</sub> / S <sub>200</sub>	
Ability to release	NPD released	
Self-closing (only for self-closing fire and/or smoke control door and/or windows)	NPD C	EN 16034:2014
Durability of ability to release	NPD	
Durability of self-closing (only for self-closing fire and/or smoke control door and/or windows)  - regarding loss of quality (Durability)  - regarding aging (Corrosion)	- NPD / 5 - NPD / achieved	
Ability to release	Requirement fulfilled	EN 14351-1: 2006+A2:2016