## **Certificate of Constancy** of Performance



Basis:

EN 16034

EN 14351-1

Certificate n°: 0757-CPR-277-9015760-2-1

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

> Pedestrian doorsets, industrial/commercial/ garage doors with fire resistance and smoke control characteristics

Schüco ADS 80 FR 60 Trade name

> Pedestrian doorset according to EN 14351-1:2006+A2:2016 with fire resistance and smoke control characteristics according to EN 16034:2014

Construction and classification: see EXAP report n°

18-002403-PR01 and classification report no 18-002403-PR02 Levels and classes of

According to configuration in annex 1 - Installation in residential and non-residential construction

- In the case of room partitioning into fire and/or smoke protection

sections and/or escape routes

placed on the market Walsin Ltd under the name or trade

Product description/

specification

performance

Intended use(s)

24 Pine Hill Saintfield Road, IE-BT27 5PL Lisburn mark of

and produced in the Walsin Ltd manufacturing plant(s) 24 Pine Hill Saintfield Road, IE-BT27 5PL Lisburn

Notified body No. 0757 EC-Reference-No.

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

## EN 14351-1:2006+A2:2016 and EN 16034:2014

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on 17.08.2022 and will remain valid until 05.02.2026, as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

The use of this certificate and the marking of the products are bound by an existing certification and surveillance contract with the ift Rosenheim no. 277 9015760.

www.ec.europa.eu

**Identity check** 



www.ift-rosenheim.de/ ift-zertifiziert ID: 2FB-56C56

/e-Zer-6274-de / 01.08.2022



Contact Phone: +49 8031 261-0 Fax: +49 8031 261-290

www.ift-rosenheim.de



Testing and Calibration – EN ISO/IEC 17025 Inspection – EN ISO/IEC 17020 Product Certification – EN ISO/IEC 17065 Certification of Management Systems - EN ISO/IEC 17021





## **Certificate of constancy of performance**

Annex 1 Page 1 of 1
Certificate holder: Walsin Ltd
Date of issue: 06.02.2023



Certificate n°: 0757-CPR-277-9015760-2-1

## **Product description:**

Essential characteristics according to EN 16034	Performance
Fire resistance (in the case of room partitioning into fire and/or smoke protection sections)	NPD / E 15 / E 20 / E 30 / E 45 / E 60 NPD / EW 15 / EW 20 / EW 30 / EW 45 / EW 60 NPD / El <sub>2</sub> 15 / El <sub>2</sub> 20 / El <sub>2</sub> 30 / El <sub>2</sub> 45 / El <sub>2</sub> 60 NPD / El <sub>1</sub> 15 / El <sub>1</sub> 20 / El <sub>1</sub> 30
Smoke control (only for applications where smoke spread limitation is required)	NPD / S <sub>a</sub> / S <sub>200</sub>
Ability to release	NPD / Released
Self-closing action (only for self-closing fire and/or smoke protection doors and/or windows)	NPD / C
Durability of ability to release	NPD / Maintain release
Durability of self-closing  (only for self-closing fire and/or smoke protection doors and/or windows)  - Compared with loss of quality (resistance to repeated opening and closing)  - Compared with ageing (corrosion)	NPD / 0 / 1 / 2 / 3 / 4 / 5 NPD / Achieved