

Certificate of Constancy of Performance



Certificate n°: 0757-CPR-280SB-6080181-2-1

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

Internal doors made of steel sheet with fire and smoke protection properties

Trade name	"H30-1"
Specification	Construction and classification: ETA-24/0098 dated 16.04.2024
Levels and classes of performance	as per Annex 1
Intended use	as opening closure in fire-resistant walls and/or escape routes inside of buildings
Placed on the market under the name or trade mark of	Hörmann KG Verkaufsgesellschaft Upheider Weg 94-98, DE-33803 Steinhagen
Manufacturing plant(s)	Hörmann KG Freisen Bahnhofstr. 43, DE-66629 Freisen
Notified Body EC reference n°	0757

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in

EAD 020029-00-1102:2017-04



under system 1 for the performance set out in the European technical approval (ETA) are applied and that the factory production control conducted by the manufacturer is assessed to ensure the **constancy of performance of the construction product**.

This certificate was first issued on 26.04.2024 and will remain valid until 25.04.2027, as long as neither ETA, the European Assessment Document (EAD), the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

The use of this certificate and the marking of the products are bound by an existing certification and surveillance contract with the ift Rosenheim n° 280SB 6080181.

Christian Kehrer

Christian Kehrer
Head of notified product certification body
ift Rosenheim
26.04.2024



www.ec.europa.eu

Identity-Check



www.ift-rosenheim.de/
ift-certified
ID: 11F-44B69

Certificate of Constancy of Performance

Annex 1
Manufacturer: **Hörmann KG**
Date of issue: **26.04.2024**



Certificate n°: 0757-CPR-280SB-6080181-2-1

Product description:

Essential characteristics	Performance*
Reaction to fire of components	Steel sheet A1 Mineral fibre inserts A1 Plasterboards A2 Intumescent building materials B1
Fire resistance (in the case of room partitioning into fire and/or smoke protection sections)	NPD / E 15 / E 20 / E 30 NPD / EW 15 / EW 20 / EW 30 NPD / EI ₂ 15 / EI ₂ 20 / EI ₂ 30
Smoke control	NPD / S _a / S ₂₀₀
Ability to release	NPD / released
Self-closing action	NPD / C
Durability of ability to release	NPD/Maintain release
Durability of self-closing (only for self-closing fire and/or smoke protection doors and/or windows) – Compared with loss of quality (resistance to repeated opening and closing) – Compared with ageing (corrosion)	NPD / 0 / 1 / 2 / 3 / 4 / 5 NPD / achieved
Impact resistance	NPD
Resistance	NPD

* The performances/values have been taken from ETA-24/0098 dated 16.04.2024.