

Certificate of Constancy of Performance



Certificate No.: 0757-CPR-695B-8006510-2-1

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

Basis:

EN 14449-2005-05/AC:2005-10

Laminated glass and laminated safety glass with requirements for fire resistance

Product description/
specification

Pyrobel 16 / Pyrobel 16 DGU

See documentary evidence no. 21-004289-PR01

Levels and classes of
performance

EI 30

Intended use(s)

Intended for use in buildings and other works with requirements for fire resistance in accordance with EN 13501-2 : 2007 + A1 : 2009

placed on the market
under the name or trade
mark of

PL-Glass Oy

Sahatie 1, FI-74700 Kiuruvesi

and produced in the
manufacturing plant(s)

PL-Glass Oy

Sahatie 1, FI-74700 Kiuruvesi

Notified body No.
EC-Reference-No.

0757

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)


EN 14449 : 2005

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the **constancy of performance of the construction product**.

This certificate was first issued on 13.12.2022 and will remain valid until 12.12.2025, as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

The use of this certificate and the marking of the products are bound by an existing certification and surveillance contract with the **ift** Rosenheim no. 695B 8006510.

Christian Kehrer
Christian Kehrer
Head of notified product certification body
ift Rosenheim
13.12.2022



www.ec.europa.eu

Identity check



www.ift-rosenheim.de/
ift-zertifiziert
ID: 232-4BDF8