

Certificate of Constancy of Performance



Certificate n°: 0757-CPR-277-9038742-1-1

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

Basis:

EN 16034
EN 14351-1

pedestrian doorsets with fire resistance

Trade name

M84 FR Alumil

pedestrian doorset according to EN 14351-1:2006+A2:2016 with fire resistance according to EN 16034:2014

Product description/
specification

Construction and classification: see EXAP report n°
FIRES-ER-048-22-NURE dated 14.12.22
and classification reports n°
FIRES-CR-271-22-NURE dated 14.12.22,
FIRES-CR-194-21-AUPE dated 05.08.2021,
FIRES-CR-195-21-AUPE dated 05.08.2021,
FIRES-CR-196-21-AUPE dated 13.09.2021,
FIRES-CR-197-21-AUPE dated 13.09.2021

Levels and classes of
performance

According to configuration in **annex 1**

Intended use(s)

- Installation in residential and non-residential construction
- In the case of room partitioning into fire and/or smoke protection sections and/or escape routes

placed on the market
under the name or trade
mark of

paMIL P.C.

PROASTEIO, GR-58200 Edessa

and produced in the
manufacturing plant(s)

paMIL P.C.

PROASTEIO, GR-58200 Edessa

Notified body No.
EC-Reference-No.

0757


This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 14351-1:2006+A2:2016 and EN 16034:2014

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the **constancy of performance of the construction product**.

This certificate was first issued on 12.05.2023 and will remain valid until 11.05.2026, as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

The use of this certificate and the marking of the products are bound by an existing certification and surveillance contract with the **ift** Rosenheim no. 277 9038742.



www.ec.europa.eu

Identity check



www.ift-rosenheim.de/
ift-zertifiziert
ID: 65C-3A87A

Christian Kehrer

Christian Kehrer
Head of notified product certification body
ift Rosenheim
12.05.2023



Certificate of constancy of performance

Annex 1
Certificate holder: paMIL P.C.
Date of issue: 12.05.2023



Certificate n°: 0757-CPR-277-9038742-1-1

Product description:

Essential characteristics according to EN 16034	Performance
Fire resistance⁴⁾ (in the case of room partitioning into fire and/or smoke protection sections)	npd E 15, E 20, E 30, E 45, E 60 EW 20, EW 30, EW 60 EI ₁ 15, EI ₁ 20, EI ₁ 30, EI ₁ 45, (EI ₁ 60) ²⁾³⁾ EI ₂ 15, EI ₂ 20, EI ₂ 30, EI ₂ 45, EI ₂ 60 ³⁾
Smoke control (only for applications where smoke spread limitation is required)	NPD
Ability to release¹⁾	NPD
Self-closing action (only for self-closing fire and/or smoke protection doors and/or windows)	NPD / C
Durability of ability to release	NPD
Durability of self-closing (only for self-closing fire and/or smoke protection doors and/or windows) – Compared with loss of quality (resistance to repeated opening and closing) – Compared with ageing (corrosion) ¹⁾	NPD NPD / Achieved

¹⁾ In compliance with the requirements of EN 16034.

²⁾ When installed in glazing type M84 FR Alumil, the classification is achieved only up to EI₁45, otherwise EI₁60

³⁾ When using Polflam glass, the classification is achieved only up to EI_{1/2}45.

⁴⁾ Classification of the door when using insulating glass is limited to a fire load on the side of the fire protection package.