

Certificate of Constancy of Performance



Certificate No.: 0757-CPR-229PANIK-7031575-2-7

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

Basis:

EN 179:2008-01

Emergency exit devices

Product description/
specification

**Safe E611 Eneo CF, Safe P600,
Safe E601-Eneo AF, Safe P603-Tandeo F,
Safe A700 Tandeo F, Safe E700 Eneo AF**

According to configuration in **annex 1**

Levels and classes of
performance

According to configuration in **annex 1**

Intended use(s)

Intended for use on doors in escape routes without requirements for fire resistance and smoke control

placed on the market
under the name or trade
mark of

ROTO FRANK AUSTRIA GmbH

Lapp-Finze-Str. 21, AT-8401 Kalsdorf bei Graz

and produced in the
manufacturing plant(s)

ROTO FRANK AUSTRIA GmbH

Lapp-Finze-Str. 21, AT-8401 Kalsdorf bei Graz

Notified body No.
EC-Reference-No.

0757

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 179 : 2008


under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the **constancy of performance of the construction product**.

This certificate was first issued on 26.01.2016 and will remain valid until 25.01.2025, as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

The use of this certificate and the marking of the products are bound by an existing certification and surveillance contract with the ift Rosenheim no. 229PANIK 7031575.

Christian Kehrer

Christian Kehrer
Head of notified product certification body
ift Rosenheim
26.05.2023



www.ec.europa.eu

Identity check



www.ift-rosenheim.de/
ift-zertifiziert
ID: 7E4-B475B

Certificate of constancy of performance

Annex 1 Page 1 of 6
Certificate holder: ROTO-FRANK AUSTRIA GmbH
Date of issue: 26.01.2022



Certificate No.: 0757-CPR-229PANIK-7031575-2-7

Installation of the emergency exit closures:

For actuation type A (handlebar actuation)

Classification:	3	7	5	0	1	3*	5	2	A	B
------------------------	----------	----------	----------	----------	----------	-----------	----------	----------	----------	----------

Classification:	3	7	5	0	1	3*	5	2	A	D
------------------------	----------	----------	----------	----------	----------	-----------	----------	----------	----------	----------

Reference- test reports: No. 15-004017-PR01 dated 26.01.2016 and 04.02.2016
No. 120003793.02 dated 06.12.2011

Lockings:

Designation	Scope	Pin size	Function	Distance	Overlap (in mm)	Strike plates	Hole
Safe E611 Eneo CF	B and D	35 mm up to 80 mm	I	92 mm	F16 F20 F22 F24 U24 U25 U29 U32 U35 U38	F/R strike plate Combination strike plates Special strike plates	PZ

External fitting / internal fitting:

No.	Manufacturer	Coding
1.	Hoppe Holding AG	DO 20.5 DO 20.7 DO 20.20

Certificate of constancy of performance

Annex 1
Certificate holder: ROTO-FRANK AUSTRIA GmbH
Date of issue: 26.01.2022



Certificate No.: 0757-CPR-229PANIK-7031575-2-7

For actuation type A (handlebar actuation)

Classification:	3	6	5	0	1	3	2	2	A	B
------------------------	----------	----------	----------	----------	----------	----------	----------	----------	----------	----------

Classification:	3	6	5	0	1	3	2	2	A	D
------------------------	----------	----------	----------	----------	----------	----------	----------	----------	----------	----------

Reference – test reports: No. 16-002901-PR01 dated 16.11.2016

Lockings:

Designation	Scope	Pin size	Function	Distance	Overlap (in mm)	Strike plates	Hole
Safe E601-Eneo AF	B and D	35 mm up to 80 mm	I	92 mm	F16 F20 F22 F24 U24 U25 U29 U32 U35 U38	F/R strike plate	PZ
Safe P603- Tandeo F						Automatic strike plates Special strike plates	

External fitting / internal fitting:

No.	Manufacturer	Type	Coding
1.	Hoppe Holding AG	FS-86G	
		-/-	DO 20.20.01 DO 20.20.02 DO 20.20.02-RD DO 20.5.01 DO 20.5.02 DO 20.5.02-RD DO 20.7.01 DO 20.7.02

Certificate of constancy of performance

Annex 1 Page 3 of 6
Certificate holder: ROTO-FRANK AUSTRIA GmbH
Date of issue: 26.01.2022



Certificate No.: 0757-CPR-229PANIK-7031575-2-7

For actuation type A (handlebar actuation)

Classification:	3	7	5	0	1	3	2	2	A	B
------------------------	---	---	---	---	---	---	---	---	---	---

Classification:	3	7	5	0	1	3	2	2	A	D
------------------------	---	---	---	---	---	---	---	---	---	---

Reference – test reports: No. 120003793.02 dated 06.12.2011

Lockings:

Designation	Scope	Pin size	Function	Distance	Overlap (in mm)	Strike plates	Hole
Safe P600	B and D	35 mm up to 80 mm	I	92 mm	F16 F20 F22 F24 U24 U25 U29 U32 U35 U38	F/R strike plate Combination strike plates Special strike plates	PZ

External fitting / internal fitting:

No.	Manufacturer	Coding
1.	Hoppe Holding AG	DO 20.5.02 DO 20.7.02 DO 20.20.02
2.	HEWI	DO 20.13.02
3.	FSB	DO 20.3.02

Certificate of constancy of performance

Annex 1 Page 4 of 6
Certificate holder: ROTO-FRANK AUSTRIA GmbH
Date of issue: 26.01.2022



Certificate No.: 0757-CPR-229PANIK-7031575-2-7

For actuation type A (handlebar actuation)

Classification:	3	7	5	0	1	3	5	2	A	B
------------------------	----------	----------	----------	----------	----------	----------	----------	----------	----------	----------

Classification:	3	7	5	0	1	3	5	2	A	D
------------------------	----------	----------	----------	----------	----------	----------	----------	----------	----------	----------

Reference – test reports: Nr. 23-001998-PR03 dated 23.05.2023

Lockings:

Designation	Scope	Pin size	Function	Distance	Overlap (in mm)	Strike plates	Hole
Safe A700 Tandeo F Safe E700 Eneo AF	B and D	35 mm up to 65 mm	I	92 mm	F16 F20 F22 F24 U24 U25 U29 U32 U35 U38	F/R strike plate Combination strike plates Special strike plates	PZ

External fitting / internal fitting:

No.	Manufacturer	Coding
1.	Hoppe Holding AG	DO 20.5.02 DO 20.7.02 DO 20.20.02

Alternative- Special equipment, special designs

1. Safety devices

There is no objection to securing the emergency exit locks with the GFS door guard, EN 179 single-handed version.

Manufacturer: GfS Gesellschaft für Sicherheitstechnik mbH
Tempowerkring 15
21079 Hamburg, Germany

2. Special strike plate/door opener

As an alternative to the standard striking plates, the locks may be operated with electric strike strikes of the series

IST: FT 200, FT 201, FT 500, FT 501, R 7000, R 7001, A 7000
Effeff: 142, 143, 131, 111, 19, 116, 118, 119, 611
DORMA: Fire 447 und Smoke 117

or optionally with the exchange piece

"effeff 14210-00".

Certificate of constancy of performance

Annex 1
Certificate holder: ROTO-FRANK AUSTRIA GmbH
Date of issue: 26.01.2022



Certificate No.: 0757-CPR-229PANIK-7031575-2-7

Explanations:

- Description: Automatic, during closing, self-locking mortise locks with escape door function (panic function) and split cross latch. The bolt is located at the centre between the two latch parts.
- Function I: Solid lock follower, continuous escape door function from inside. Opening from inside is always possible using the internal hardware. Opening from outside is possible with action of the key on the latchbolt.
*with additional monitoring contacts integrated in the lock
- Function II: Split lock follower, continuous escape door function from inside. Opening from inside is always possible using the internal hardware. The external hardware, and/or the external follower part are engaged and disengaged by electronic control. Special hardware with a split bolt is required.
- Function IM: Solid lock follower, continuous escape door function from inside. Opening from inside is always possible using the internal hardware. Opening from outside is possible with action of the key on the latchbolt. Motorised bolt drive.
*motor-driven unlocking function of active leaf and inactive leaf
- Locking cylinder: Use of any type of locking cylinder with free turn facility does not have any effect on due operation.