

Certificate of Constancy of Performance



Certificate No.: 0757-CPR-229PANIK-6039631-22-5

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

Basis:

EN 1125:2008-01

Panic exit devices

mFlipLock, sFlipLock

Panik exit devices

operated by a horizontal bar for single and double leaf doorsets

According to configuration in **annex 1**

According to configuration in **annex 1**

Intended for use on doors in escape routes with requirements for fire resistance and smoke control

Product description/
specification

Levels and classes of
performance

Intended use(s)

placed on the market
under the name or trade
mark of

and produced in the
manufacturing plant(s)

Notified body No.
EC-Reference-No.

ASSA ABLOY (Schweiz) AG Schlosstechnik

Laufenstr. 172, CH-4245 Kleinlützel

ASSA ABLOY (Schweiz) AG Schlosstechnik

Laufenstr. 172, CH-4245 Kleinlützel

0757

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 1125 : 2008

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the **constancy of performance of the construction product**.

This certificate was first issued on 13.12.2017 and will remain valid until 12.12.2023, as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

The use of this certificate and the marking of the products are bound by an existing certification and surveillance contract with the **ift** Rosenheim no. 229PANIK 6039631.




Prof. Jörn P. Lass
Director

ift Rosenheim
13.12.2020



Christian Kehrer

Christian Kehrer
Head of notified product certification body



www.ec.europa.eu



www.ift-rosenheim.de

Certificate of constancy of performance

Annex 1 Page 1 of 17
Certificate holder: ASSA ABLOY (Schweiz) AG
Date of issue: 13.12.2020



Certificate No.: 0757-CPR-229PANIK-6039631-22-5

1. Panic exit devices as per EN 1125 : 2008 for single leaf doorsets: horizontal push/handlebar operation

For operation mode A (handlebar operation)

For operation mode B (pressure bar - operation)

Classification:	3	7	6	B	1	3	2	1*/2*	A*/B	B
------------------------	----------	----------	----------	----------	----------	----------	----------	--------------	-------------	----------

***Classification depending on the hardware used**

For Assa Abloy:

Back set 30 up to 80 mm
Distance 92 mm for PZ and 94 mm for RZ
Forend (18 up to 24) mm x 3 mm

For Wicona:

Back set 35 up to 45 mm
Distance 92 mm for PZ and 94 mm for RZ
Forend 22 mm x 3 mm

Intended use: for use on doors with smoke and fire protection requirements,
as well as on doors in escape and rescue routes

Reference-report: No. 17-000296-PR04 dated 17. November 2017

Reference-report: No. 17-000296-PR09 dated 17. November 2017

Certificate of constancy of performance

Annex 1 Page 2 of 17
 Certificate holder: ASSA ABLOY (Schweiz) AG
 Date of issue: 13.12.2020



Certificate No.: 0757-CPR-229PANIK-6039631-22-5

Locks:

- mFlipLock basis
- mFlipLock standard
- mFlipLock check contact lock
- mFlipLock drive motor lock
- mFlipLock access motor lock
- mFlipLock e-drive handle controlled
- mFlipLock e-access handle controlled

Family	Designation Assa Abloy	Designation Wicona
mFlipLock / basis	23444PE .6 / .7	6020784, 6020785, 6020786, 6020787
	23446PBa .2 / .3	6020736, 6020737, 6020738, 6020739
mFlipLock / standard	24444PE .6 / .7	6020788, 6020789, 602 0790, 6020791
	24446PBa .2 / .3	6020792, 6020793, 6020794, 6020795
	24544PE-SV .6 / .7	6020926, 6020927, 6020928, 6020929
	24444PE-TF .6 / .7	6022921, 6022922, 6022923, 6022924
	24544PE-SV-TF .6 / .7	6020808, 6020809, 6020810, 6020811
	24546PBa-SV .2 / .3	6022913, 6022914, 6022915, 6022916
mFlipLock check / contact lock	24476PBa .2 / .3	6020934, 6020935, 6020936, 6020937
	24474PE .6 / .7	6020930, 6020931, 6020932, 6020933
	24574PE-SV .6 / .7	6020942, 6020943, 6020944, 6020945
	24574PE-SV-TF .6 / .7	6020966, 6020967, 6020968, 6020969
	24576PBa-SV .2 / .3	6020946, 6020947, 6020948, 6020949
mFlipLock drive motor lock	25544PE-SV .6 / .7	6020812, 6020813, 6020814, 6020815
mFlipLock access motor lock / with evaluation contacts	25574PE-SV .6 / .7	6020954, 6020955, 6020956, 6020957
mFlipLock e-drive / handle controlled motor lock	26546PBa-SV .2 / .3	6023513, 6023514, 6023515, 6023516
mFlipLock e-access / Handle controlled motor with evaluation contacts	26576PBa-SV .2 / .3	6023529, 6023530, 6023531, 6023532

Certificate of constancy of performance

Annex 1 Page 3 of 17
 Certificate holder: ASSA ABLOY (Schweiz) AG
 Date of issue: 13.12.2020



Certificate No.: 0757-CPR-229PANIK-6039631-22-5

Accessories:

No.	Designation Firma Assa Abloy	Type	Wicona No.
1.	XL- forend extensions	Lengths of 350 mm, 550 mm und 800 mm Widths of forends 18 mm - 24 mm x 3 mm	6022994, 6022995, 6020766, 6020767, 6022997, 6022998, 6024116, 6024117, 6024118, 6024119, 6024120, 6024121
2.	Flap striking plate	B-23421.HRE1243 B-23421.HRE4233 B-23421.RE3243 B-23421.RE6233 B-23421.R9243 B-24421.R9243 BV-24421.HR3243 BV-24421.HR3733 BV-24421.R3733 BV-24421.HR6233-24 BV-24421.HR6233-29,5 BV-24421.R6233-29,5 BV-24421.R6233-24 BV-24421.R3243	6020735, 6022902, 6022903, 6023410, 6023861
3.	Angled striking plate	B-23421.HRE1141/42 B-23421.HRE4131/42 B-23421.RE3141/42 B-23421.RE6131/32 B-23421.R9141/42 B-24421.R9141/42 BV-24421.R3631/32 BV-24421.HR3141/42 BV-24421.HR3631/32 BV-24421.R3141/42 BV-24421.R3641/42	-/-

Certificate of constancy of performance

Annex 1 Page 4 of 17
 Certificate holder: ASSA ABLOY (Schweiz) AG
 Date of issue: 13.12.2020



Certificate No.: 0757-CPR-229PANIK-6039631-22-5

4.	Flat striking plate	B-23421.HRE7333 B-23421.RE5333-24 B-23421.RE9333 B-23421.R9333 BV-24421.HR6333 BV-24421.R5333-20 BV-24421.R5333-24 BV-24421.R6333 BV-25574.RE-FF.5333-20e BV-25574.RE-FF.5333-24e	6020768, 6020769, 6023396, 6023397, 6023411
5.	U- Strike plate	B-23421.RE5931/32-24 B-23421.R9931/32-24 B-24421.R9931/32-24 BV-24421.HR6931/32-24 BV-24421.R6931/32-22 BV-24421.HR6931/32-22 BV-24421.R5931/32-24, BV-24421.R6931/32-22 BV-24421.R6931/32-24 BV-25574.RE-FF.5931/32-24U	-/-
6.	Milling strike plate	BV-23421.E3541/42-20 BV-23421.2541/42-20 BV-23421.3541/42-20 BV-23421.E3541/42-20 BV-24413.3541/42-20 BV-24421.H3541/42-20 BV-24421.2541/42-20	-/-

Certificate of constancy of performance

Annex 1 Page 5 of 17
 Certificate holder: ASSA ABLOY (Schweiz) AG
 Date of issue: 13.12.2020



Certificate No.: 0757-CPR-229PANIK-6039631-22-5

Locks:

- sFlipLock basis
- sFlipLock standard
- sFlipLock check contact lock
- sFlipLock drive motor lock
- sFlipLock access motor lock
- sFlipLock e-drive handle controlled
- sFlipLock e-access handle controlled

Family	Designation Assa Abloy	Designation Wicona
sFlipLock / basis	13444PE .6 / .7	6023951, 6023952, 6023953, 6023954, 6023955, 6023956, 6023957, 6023958
	13446PBa .2 / .3	6023967, 6023968, 6023969, 6023970, 6023975, 6023976, 6023977, 6023778
sFlipLock / standard	14444PE .6 / .7	6023959, 6023960, 6023961, 6023962, 6023963, 6023964, 6023965, 6023966
	14446PBa .2 / .3	6023991, 6023992, 6023993, 6023994 6023999, 6024000, 6024001, 6024002
	14544PE-SV .6 / .7	6024031, 6024032, 6024033, 6024034, 6024035, 6024036, 6024037, 6024038
	14444PE-TF	6023983, 6023984, 6023985, 6023986, 6023987, 6023988, 6023989, 6023990, 6024091
	14544PE-SV-TF .6 / .7	6023354, 6023355, 6023356, 6023357, 6024039, 6024040, 6024041, 6024042
	14546PBa-SV .2 / .3	6024043, 6024044, 6024045, 6024046 6024051, 6024052, 6024053, 6024054

Certificate of constancy of performance

Annex 1 Page 6 of 17
 Certificate holder: ASSA ABLOY (Schweiz) AG
 Date of issue: 13.12.2020



Certificate No.: 0757-CPR-229PANIK-6039631-22-5

sFlipLock check / contact lock	14476PBa .2 / .3	6024015, 6024016, 6024017, 6024018 6024023, 6024024, 6024025, 6024026
	14474PE .6 / .7	6024007, 6024008, 6024009, 6024010, 6024011, 6024012, 6024013, 6024014
	14574PE-SV .6 / .7	6024059, 6024060, 6024061, 6024062, 6024063, 6024064, 6024065, 6024066
	14574PE-SV-TF .6 / .7	6024083, 6024084, 6024085, 6024086, 6024087, 6024088, 6024089, 6024090
	14576PBa-SV .2 / .3	6024067, 6024068, 6024069, 6024070 6024075, 6024076, 6024077, 6024078
sFlipLock drive motor lock	15544PE-SV .6 / .7	6023328, 6023329, 6023330, 6023331, 6023358, 6023359, 6023360, 6023361
sFlipLock access motor lock / with evaluation contacts	15574PE-SV .6 / .7	6023337, 6023338, 6023339, 6023340, 6023366, 6023367, 6023368, 6023369
sFlipLock e-drive / handle controlled motor lock	16546PBa-SV .2 / .3	6023332, 6023333, 6023334, 6023335 6023362, 6023363, 6023364, 6023365
sFlipLock e-access / handle controlled motor lock with evaluation contacts	16576PBa-SV .2 / .3	6023341, 6023342, 6023343, 6023344 6023370, 6023371, 6023372, 6023373

Certificate of constancy of performance

Annex 1 Page 7 of 17
Certificate holder: ASSA ABLOY (Schweiz) AG
Date of issue: 13.12.2020



Certificate No.: 0757-CPR-229PANIK-6039631-22-5

Accessories:

No.	Designation Firma Assa Abloy	Type	Wicona No.
1.	Flap striking plate	BV-14421.H3243 BV-14421.R6233-24 BV-14421.R6233-29,5	6020735, 6022902, 6022903, 6023410, 6023861
2.	Angled striking plate	BV-14421.R3141-42 BV-14421.R3631-32	-/-
3.	Flat striking plate	BV-14421.R6333 BV-14421.R6833	6020768, 6020769, 6023396, 6023397, 6023411
4.	U-Strike plate	BV-14421.R6931/32-24	-/-
5.	Milling strike plate	BV-14421.3541/42-20	-/-

Certificate of constancy of performance

Annex 1 Page 8 of 17
Certificate holder: ASSA ABLOY (Schweiz) AG
Date of issue: 13.12.2020



Certificate No.: 0757-CPR-229PANIK-6039631-22-5

2. Panic exit devices as per EN 1125 : 2008 for double leaf doorsets: horizontal push/handlebar operation

For operation mode A (handlebar operation)

For operation mode B (pressure bar - operation)

Classification:	3	7	7	B	1	3	2	1*/2*	A*/B	A
------------------------	----------	----------	----------	----------	----------	----------	----------	--------------	-------------	----------

***Classification depending on the hardware used**

For Assa Abloy:

Back set 30 up to 80 mm
Distance 92 mm for PZ and 94 mm for RZ
Forend (18 up to 24) mm x 3 mm

For Wicona:

Back set 35 and 45 mm
Distance 92 mm for PZ and 94 mm for RZ
Forend 22 mm x 3 mm

Intended use: for use on doors with smoke and fire protection requirements, as well as on doors in escape and rescue routes

Reference-report: No. 17-000296-PR06 dated 12. December 2017

Reference-report: No. 17-000296-PR13 dated 12. December 2017

Certificate of constancy of performance

Annex 1 Page 9 of 17
 Certificate holder: ASSA ABLOY (Schweiz) AG
 Date of issue: 13.12.2020



Certificate No.: 0757-CPR-229PANIK-6039631-22-5

Locks:

- mFlipLock basis
- mFlipLock standard
- mFlipLock check contact lock
- mFlipLock drive motor lock
- mFlipLock access motor lock
- mFlipLock e-drive handle controlled
- mFlipLock e-access handle controlled

Family	Designation Assa Abloy	Designation Wicona
mFlipLock / standard	24444PE-ZF .6 / .7	6022925, 6022926, 6022927, 6022928
	24444HR-PE-TF-ZF .6/.7	6023637, 6023638, 6023639, 6023640, 6023653, 6023654, 6023655, 6023656
	24444PE-TF-ZF .6/.7	6022989, 6022990, 6022991, 6022992
	24444HR-PE-ZF .6 / .7	6023633, 6023634, 6023635, 6023636, 6023649, 6023650, 6023651, 6023652
	24446PBa-ZF .2 / .3	6022929, 6022930, 6022931, 6022932
	24446HR-PBa-ZF .2 / .8	6023641, 6023642, 6023643, 6023644, 6023657, 6023658, 6023659, 6023660
	24544PE-SV-ZF .6 / .7	6022977, 6022978, 6022979, 6022980
	24544PE-SV-TF-ZF .6 / .7	6022937, 6022938, 6022939, 6022940
	24544HR-PE-SV-ZF .6 / .7	6023346, 6023347, 6023348, 6023349, 6023386, 6023387, 6023388, 6023389
	24544HR-PE-SV-TF-ZF .6 / .7	6023665, 6023666, 6023667, 6023668, 6023673, 6023674, 6023675, 6023676
	24546HR-PBa-SV-ZF .2/.3	6023390, 6023391, 6023392, 6023393, 6023350, 6023351, 6023352, 6023353
	24546PBa-SV-ZF .2 / .3	6022981, 6022982, 6022983, 6022984

Certificate of constancy of performance

Annex 1 Page 10 of 17
 Certificate holder: ASSA ABLOY (Schweiz) AG
 Date of issue: 13.12.2020



Certificate No.: 0757-CPR-229PANIK-6039631-22-5

mFlipLock check / contact lock	24474PE-ZF.6 / .7	6022949, 6022950, 6022951, 6022952
	24474HR-PE-ZF .6 / .7	6023681, 6023682, 6023683, 6023684, 6023693, 6023694, 6023695, 6023696
	24476PBa-ZF .2 / .3	6022953, 6022954, 6022955, 6022956
	24476HR-PBa-ZF .2 / .3	6023685, 6023686, 6023687, 6023688, 6023697, 6023698, 6023699, 6023700
	24574PE-SV-ZF .6 / .7	6022965, 6022966, 6022967, 6022968
	24574PE-SV-FF-ZF .6 / .7	6023705, 6023707, 6023706, 6023708
	24574PE-SV-TF-ZF .6 / .7	6022961, 6022962, 6022963, 6022964
	24576PBa-SV-ZF .2 / .3	6022969, 6022970, 6022971, 6022972
	24574HR-PE-SV-ZF.6 / .7	6023709, 6023710, 6023711, 6023712, 6023729, 6023730, 6023731, 6023732
	24576HR-PBa-SV-ZF .2 / .3	6023721, 6023722, 6023723, 6023724, 6023741, 6023742, 6023743, 6023744
	24576HR-PBa-SV-FF-ZF .2/.3	6020075, 6020076, 6020077, 6020078, 6020079, 6020080, 6020081, 6020082
	24574HR-PE-SV-TF-ZF.6 / .7	6023717, 6023718, 6023719, 6023720, 6023737, 6023738, 6023739, 6023740
	24574HR-PE-SV-FF-ZF .6 / .7	6023713, 6023714, 6023715, 6023716, 6023733, 6023734, 6023735, 6023736
mFlipLock drive motor lock	25544PE-SV-ZF .6 / .7	6022941, 6022942, 6022943, 6022944
	25544HR-PE-SV-ZF .6 / .7	6023753, 6023754, 6023755, 6023756, 6023765, 602366, 6023767, 6023768

Certificate of constancy of performance

Annex 1 Page 11 of 17
 Certificate holder: ASSA ABLOY (Schweiz) AG
 Date of issue: 13.12.2020



Certificate No.: 0757-CPR-229PANIK-6039631-22-5

mFlipLock access motor lock / with evaluation contacts	25574PE-SV-ZF .6 / .7	6022945, 6022946, 6022947, 6022948
	25574PE-SV-FF-ZF .6 / .7	6023749, 6023750, 6023751, 6023752
	25574HR-PE-SV-ZF .6 / .7	6023757, 6023758, 6023759, 6023760, 6023769, 6023770, 6023771, 6023772
	25574HR-PE-SV-FF-ZF .6 / .7	6023761, 6023762, 6023763, 6023764, 6023773, 6023774, 6023775, 6023776
mFlipLock e-drive / handle controlled motor lock	26546PBa-SV-ZF .2 / .3	6023777, 6023778, 6023779, 6023780
	26546HR-PBa-SV-ZF .2/.3	6023793, 6023794, 6023795, 6023796, 6023809, 6023810, 6023811, 60238012
mFlipLock e-access / controlled motor lock with evaluation contacts	26576PBa-SV-ZF .2 / .3	6023785, 6023786, 6023787, 6023788
	26576HR-PBa-SV-ZF .2 / .3	6023801, 6023802, 6023803, 6023804, 6023817, 6023818, 6023819, 6023820
	26576HR-PBa-SV-FF-ZF .2/.3	6020083, 6020084, 6020085, 6020086, 6020087, 6020088, 6020089, 6020090

Accessories:

No.	Designation Firma Assa Abloy	Type	Wicono No.
1.	XL- forend extensions	Length of 350 mm, 550mm and 800 mm Widths of forends 18 mm - 24 mm x 3 mm	6022994, 6022995, 6020766, 6020767, 6022997, 6022998, 6024116, 6024117, 6024118, 6024119, 6024120, 6024121
2.	Panic passive leaf locking	24413-M, 24413-M-TF, 24473-M, 24473-M-TF, 24413-H, 24413-H-TF, 24473-H, 24473-H-TF	6023012, 6023013, 6023014, 6023015, 6023008, 6023009, 6023010, 6023011, 6023004, 6023005, 6023006, 6023007, 6023000, 6023001, 6023002, 6023003, 6023394, 6023395, 6023825

Certificate of constancy of performance

Annex 1 Page 12 of 17
 Certificate holder: ASSA ABLOY (Schweiz) AG
 Date of issue: 13.12.2020



Certificate No.: 0757-CPR-229PANIK-6039631-22-5

3.	Forends to panic passive leaf locking	24413-H-STE-V.3441-42, 24413-H-STF-V.2333, 24413-H-STL-V.3243, 24413-H-STW-V.3141-42, 24413-M-STF-V.5333, 24413-M-STF-V.6333, 24413-M-STL-V.6233, 24413-M-STU-V.6931-32	6023397, 6023411, 6020735, 6023861, 6020755, 6022993, 6020756, 6020765, 6022900, 6022901, 6023264, 6023860, 6023862
4.	Floor-closing recess	1727	6920087, 6920170, 6920171, 6920048, 6920740, 6021069, 6021984, 6020729
5.	Switching lock	1730	6020773
6.	Square mandrel	5961, 5968, 5496	6030221, 6030222
7.	Bar guidance	1726	-/-
8.	Round tube	1725	6020775, 6023265
9.	Round bar	1724	6020774, 6023091
10.	Reinforcement set	1723	6024115
11.	Flap striking plate	B-23421.HRE1243 B-23421.HRE4233 B-23421.RE3243 B-23421.RE6233 B-23421.R9243 B-24421.R9243 BV-24421.HR3243 BV-24421.HR3733 BV-24421.R3733 BV-24421.HR6233-24 BV-24421.HR6233-29,5 BV-24421.R6233-29,5 BV-24421.R6233-24 BV-24421.R3243	6020735, 6022902, 6022903, 6023410, 6023861

Certificate of constancy of performance

Annex 1 Page 13 of 17
 Certificate holder: ASSA ABLOY (Schweiz) AG
 Date of issue: 13.12.2020



Certificate No.: 0757-CPR-229PANIK-6039631-22-5

12.	Angled striking plate	B-23421.HRE1141/42 B-23421.HRE4131/42 B-23421.RE3141/42 B-23421.RE6131/32 B-23421.R9141/42 B-24421.R9141/42 BV-24421.R3631/32 BV-24421.HR3141/42 BV-24421.HR3631/32 BV-24421.R3141/42 BV-24421.R3641/42	-/-
13.	Flat striking plate	B-23421.HRE7333 B-23421.RE5333-24 B-23421.RE9333 B-23421.R9333 BV-24421.HR6333 BV-24421.R5333-20 BV-24421.R5333-24 BV-24421.R6333 BV-25574.RE-FF.5333-20e BV-25574.RE-FF.5333-24e	6020768, 6020769, 6023396, 6023397, 6023411
14.	U-Strike plate	B-23421.RE5931/32-24 B-23421.R9931/32-24 B-24421.R9931/32-24 BV-24421.HR6931/32-24 BV-24421.R6931/32-22 BV-24421.HR6931/32-22 BV-24421.R5931/32-24, BV-24421.R6931/32-22 BV-24421.R6931/32-24 BV-25574.RE-FF.5931/32-24U	-/-
15.	Milling strike plate	BV-23421.E3541/42-20 BV-23421.2541/42-20 BV-23421.3541/42-20 BV-23421.E3541/42-20 BV-24413.3541/42-20 BV-24421.H3541/42-20 BV-24421.2541/42-20	-/-

Certificate of constancy of performance

Annex 1 Page 14 of 17
 Certificate holder: ASSA ABLOY (Schweiz) AG
 Date of issue: 13.12.2020



Certificate No.: 0757-CPR-229PANIK-6039631-22-5

Locks:

sFlipLock standard
 sFlipLock check contact lock
 sFlipLock drive motor lock
 sFlipLock access motor lock
 sFlipLock e-drive handle controlled
 sFlipLock e-access handle controlled

Family	Designation Assa Abloy	Designation Wicona
sFlipLock / standard	14444PE-ZF .6 / .7	6020883, 6020884, 6020885, 6020886, 6020907, 6020908, 6020909, 6020910
	14446PBa-ZF .2 / .3	6020899, 6020900, 6020901, 6020902, 6022891, 6022892, 6022893, 6022894
	14544PE-SV-ZF .6 / .7	6022933, 6022934, 6022935, 6022936, 6022973, 6022974, 6022975, 6022976,
	14544PE-SV-TF-ZF	6023432, 6023433, 6023434, 6023435
	14546PBa-SV-ZF .2 / .3	6022957, 6022958, 6022959, 6022960, 6022985, 6022986, 6022987, 6022988
	14444PE-TF-ZF	6020891, 6020892, 6020893, 6020894, 6020986, 6020987, 6020988, 6020989
sFlipLock check / contact lock	14474PE-ZF .6 / .7	6023645, 6023646, 6023647, 6023648, 6023669, 6023670, 6023671, 6023672
	14476PBa-ZF .2 / .3	6023661, 6023662, 6023663, 6023664, 6023677, 6023678, 6023679, 6023680
	14574PE-SV-ZF .6 / .7	6023689, 6023690, 6023691, 6023692, 6023745, 6023746, 6023747, 6023748
	14574PE-SV-TF-ZF .6 / .7	6023701, 6023702, 6023703, 6023704, 6023781, 6023782, 6023783, 6023784
	14576PBa-SV-ZF .2 / .3	6023725, 6023726, 6023727, 6023728, 6023789, 6023790, 6023791, 6023792
sFlipLock drive motor lock	15544PE-SV-ZF .6 / .7	6023797, 6023798, 6023799, 6023800, 6023813, 6023814 6023815, 6023816
sFlipLock access motor lock / with evaluation contacts	15574PE-SV-ZF .6 / .7	6023805, 6023806, 6023807, 6023808, 6023821, 6023822, 6023823, 6023824

Certificate of constancy of performance

Annex 1 Page 15 of 17
 Certificate holder: ASSA ABLOY (Schweiz) AG
 Date of issue: 13.12.2020



Certificate No.: 0757-CPR-229PANIK-6039631-22-5

Accessories:

No.	Designation Firma Assa Abloy	Type	Wicona No.
1.	Panic passive leaf locking	24413-M, 24413-M-TF, 24473-M, 24473-M-TF, 24413-H, 24413-H-TF, 24473-H, 24473-H-TF	6023012, 6023013, 6023014, 6023015, 6023008, 6023009, 6023010, 6023011, 6023004, 6023005, 6023006, 6023007, 6023000, 6023001, 6023002, 6023003, 6023394, 6023395, 6023825
2.	Forends to panic passive leaf locking	14413-H-STL-V.3143, 14413-H-STW-V.3141-42, 14413-M-STU-V.6931-32, 14413-M-STL-V.6233, 14413-M-STF-V.6333	6020755, 6022993, 6020756, 6020765, 6022900, 6022901, 6023264, 6023860, 6023862
3.	Floor-closing recess	1727	6920087, 6920170, 6920171, 6920048, 6920740, 6021069, 6021984, 6020729
4.	Switching lock	1730	6020773
5.	Square mandrel	5961, 5968, 5496	6030221, 6030222
6.	Bar guidance	1726	-/-
7.	Round tube	1725	6020775, 6023265
8.	Round bar	1724	6020774, 6023091
9.	Reinforcement set	1723	6024115
10.	Flap striking plate	BV-14421.H3243 BV-14421.R6233-24 BV-14421.R6233-29,5	6020735, 6022902, 6022903, 6023410, 6023861
11.	Angled striking plate	BV-14421.R3141-42 BV-14421.R3631-32	-/-
12.	Flat striking plate	BV-14421.R6333 BV-14421.R6833	6020768, 6020769, 6023396, 6023397, 6023411
13.	U-Strike plate	BV-14421.R6931/32-24	-/-
14.	Milling strike plate	BV-14421.3541/42-20	-/-

Certificate of constancy of performance

Annex 1 Page 16 of 17
Certificate holder: ASSA ABLOY (Schweiz) AG
Date of issue: 13.12.2020



Certificate No.: 0757-CPR-229PANIK-6039631-22-5

1. External or internal fitting

No.	Manufacturer	Type	Wicona No.
1.	Assa Abloy (Switzerland) AG	eBar 5980/5981/5982/5983 push bar 5971/ (5976 is single part: round tube as push bar in fitting set 5971) panic bar type A D0082004/D0082104	6030213, 6030214, 6030215, 6030232, 6030210, 6030211, 6030212, 6030233, 6060490-6060519
2.	MTS Metallbaubeschlage AG	14.2844.42.941, 14.2844.42.942, 14.2845.410	-/-
3.	Franz Schneider Brakel GmbH + Co KG	handle bar 7980	-/-
4.	ECO Schulte GmbH & Co. KG	Push Bar EPN 2000 II handle bar EPN 900 IV handle bar EPN 950	6030225, 6030226, 6030270, 6030271, 6060340, 6060342
5.	HEWI Heinrich Wilke GmbH	Panic bar PS160XA10, PS160XA20	-/-
6.	GFS-Gesellschaft fur Sicherheitstechnik mbH	eBar 700.70 up to 71, 700.73 up to 74	-/-

Field of application:

Maximum door mass:

- for "door mass" (3rd digit in the classification key) = class 6: up to 200 kg
- for "door mass" (3rd digit in the classification key) = class 7: up to 300 kg

Maximum door height: 3.000 mm

Maximum door width: 1.320 mm

Explanations: The different product families can have the following functions:

Function B:

Initial position: Function from inside and outside: Passage from both sides via the lever handle, the latch is retracted, the lock follower is engaged on both sides.

Intended use: For doors that must allow passage from inside and outside at times.

Function C:

Initial position: Function from the inside: Exit, the door can be opened at any time in the escape direction using the lever handle. Function from outside: Idle, as the follower is decoupled.

Intended use: For doors where unauthorised opening from the outside must be prevented as a matter of principle. The door cannot be left unlocked accidentally.

Function D:

Initial position: Function from inside and outside: Passage from both sides via the lever handle, the latch is retracted, the lock follower is engaged on both sides.

Intended use: For doors that must allow passage from inside and outside at times.

Function E:

Initial position: Function from the inside: Exit, the door can always be opened in escape direction. Function from outside: Only a fixed knob or push handle may be used as a fitting. The door can only be opened with the key. The latch is retracted in the process.

Intended use: For doors where unauthorised opening from the outside must be prevented as a matter of principle. The door cannot be left unlocked accidentally.

Lock cylinder: All types of locking cylinders with freewheel function have no influence on perfect functioning.

*In the course of the tests, closures with inserted profile cylinders according to DIN 18252 (PZ version) were always tested. In the case of round cylinder designs, dimensional adjustment must be made to ensure that the function of the locks is guaranteed.